PosiTest® AT 50 mm x 50 mm Tile Kit

Instruction Manual Addendum



The **PosiTest** *AT 50 mm x 50 mm Tile Kit* is designed to measure tensile strength of ceramic tile cementitious, dispersion and reaction resin adhesives in accordance with BS FN 12004-2



Steps to Perform a Pull-Off Test

1. Ceramic Tile Installation

Apply ceramic tiles to the concrete test substrate according to BS EN 12004-2

2. Glue & Dolly Application

a. Ensure the 50 mm x 50 mm steel dolly plate and ceramic tile surface is clean.

- Attach the dolly plate to the ceramic tile using epoxy adhesive. Allow the adhesive to cure per the manufacturer's instructions.
- c. Screw the dolly post fully onto the dolly plate

Post

3. Pull-off Test

- Ensure the 50 mm x 50 mm tile kit stand-off is attached to the instrument.
- b. Conduct pull-off test in accordance with PosiTest AT instruction manual.

NOTE: If unable to connect the dolly to the instrument's quick coupling, the post height can be adjusted by unscrewing the dolly post from the plate.

NOTE: Ensure the instrument is setup for the 50 mm x 50 mm dolly size.

Dolly Size & Conversion

PosiTest AT-M models with a serial number greater than 14278: Select the 50.50 dolly setting

PosiTest AT-A models with a color touch display: Select the 50mm x 50mm dolly setting. If this setting is not present, perform a gage update. See defelsko.com/update/

Conversion: Older model PosiTest *AT-M* and PosiTest *AT-A* instruments require a simple manual conversion:

Select the standard 50 mm round dolly setting to perform the test. Upon completion of the pull-off, multiply the test result by 0.7854.

4. Analysis of Test Results

Examine and report test results according to BS EN 12004-2.

Limited Warranty, Sole Remedy and Limited Liability

DeFelsko's sole warranty, remedy, and liability are the express limited warranty, remedy, and limited liability that are set forth on its website: www.defelsko.com/terms

www.defelsko.com

This manual is copyrighted with all rights reserved and may not be reproduced or transmitted, in whole or part, by any means, without written permission from DeFelsko Corporation.

DeFelsko, PosiTest, PosiTector, and PosiSoft are trademarks of DeFelsko Corporation registered in the U.S. and in other countries. Other brand or product names are trademarks or registered trademarks of their respective holders.

Every effort has been made to ensure that the information in this manual is accurate. DeFelsko is not responsible for printing or clerical errors.

